

Appl. No. 10/828,572

Amdt dated October 5, 2006

Reply to Final Office Action of June 8, 2006

RECEIVED  
CENTRAL FAX CENTER  
OCT 05 2006Amendments to the Claims

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims

1. (currently amended) A balloon catheter, comprising:  
an elongate catheter shaft having a distal end, an inflation lumen defined therein, and a guidewire lumen defined therein;  
a balloon coupled to the shaft and disposed adjacent the distal end of the shaft; and  
a traction member positioned exterior of the balloon, the traction member having a first end, a body portion, and a second end, the first end of the traction member being coupled to the balloon catheter proximate the distal end of the shaft and the body portion of the traction member extending proximally over at least a portion of the balloon, the second end of the traction member being free from attachment unattached to the balloon catheter; and  
wherein the body portion of the traction member includes one or more gripping surfaces defined in the body portion.
2. (original) The balloon catheter of claim 1, wherein the one or more gripping surfaces are defined by one or more bumps disposed on the body portion.
3. (original) The balloon catheter of claim 1, wherein the one or more gripping surfaces are defined by a helical region within the body portion.
4. (original) The balloon catheter of claim 1, wherein the one or more gripping surfaces are defined by a ridge along the body portion.
5. (original) The balloon catheter of claim 1, wherein the one or more gripping surfaces are defined by one or more saw-tooth projections along the body portion.
6. (original) The balloon catheter of claim 1, wherein the one or more gripping surfaces are defined by one or more spikes along the body portion.

Appl. No 10/828,572

Amndt dated October 5, 2006

Reply to Final Office Action of June 8, 2006

7. (original) The balloon catheter of claim 1, wherein the one or more gripping surfaces are defined by an undulation along the body portion.

8. (cancelled)

9. (original) The balloon catheter of claim 1, wherein a portion of the guidewire lumen is arranged coaxially with the balloon.

10. (original) The balloon catheter of claim 9, further comprising a guidewire disposed in the guidewire lumen and extending distally out of a distal end of the guidewire lumen.

11. (original) The balloon catheter of claim 1, wherein the first end of the traction member is coupled to the shaft.

12. (original) The balloon catheter of claim 1, wherein the first end of the traction member is coupled to the balloon.

13. (currently amended) A balloon catheter, comprising:

an elongate catheter shaft having a distal end, an inflation lumen defined therein and a guidewire lumen defined therein;

a balloon coupled to the shaft and disposed adjacent the distal end of the shaft, the balloon being substantially coaxially arranged with at least a region of the guidewire lumen; and

a non-woven traction member positioned exterior of the balloon, the traction member having a distal end coupled affixed to the balloon catheter at a position proximate the distal end of the shaft and extending in the proximal direction and a proximal end that is free from attachment unattached to the balloon catheter, the traction member being configured to provide traction between the balloon and a target site.

14. (original) The balloon catheter of claim 13, wherein the traction member includes a gripping region defined along at least a portion thereof.

Appl. No. 10/828,572

Amdt. dated October 5, 2006

Reply to Final Office Action of June 8, 2006

15. (currently amended) The balloon catheter of claim [[13]] 14, wherein the gripping region is defined by one or more bumps disposed on the traction member.
16. (currently amended) The balloon catheter of claim [[13]] 14, wherein the gripping region is defined by a helical region of the traction member.
17. (currently amended) The balloon catheter of claim [[13]] 14, wherein the gripping region is defined by a ridge along the traction member.
18. (currently amended) The balloon catheter of claim [[13]] 14, wherein the gripping region is defined by one or more saw-tooth projections along the traction member.
19. (currently amended) The balloon catheter of claim [[13]] 14, wherein the gripping region is defined by one or more spikes coupled to the traction member.
20. (currently amended) The balloon catheter of claim [[13]] 14, wherein the gripping region is defined by an undulation along the traction member.
21. (cancelled)
22. (original) The balloon catheter of claim 13, wherein a proximal end of the traction member is disposed adjacent a proximal waist of the balloon.
23. (original) The balloon catheter of claim 13, wherein a proximal end of the traction member is disposed adjacent a midpoint of the balloon.
24. (original) The balloon catheter of claim 13, wherein a proximal end of the traction member is disposed adjacent a distal waist of the balloon.
25. (currently amended) A medical device, comprising:

Appl. No. 10/828,572

Amdt. dated October 5, 2006

Reply to Final Office Action of June 8, 2006

a catheter shaft having a guidewire lumen defined therein;  
a balloon coupled to the shaft, the balloon being substantially coaxially arranged with respect to at least a region of the guidewire lumen; and  
a non-woven traction member having a distal end ~~coupled~~ affixed to the balloon catheter at a position proximate distal end of the shaft and extending in the proximal direction and along the balloon.

26. (original) The medical device of claim 25, wherein the traction member includes one or more gripping surfaces defined along at least a portion thereof.

27. (original) The medical device of claim 25, wherein the traction member includes a gripping region defined along at least a portion thereof.

28. (original) The medical device of claim 25, wherein the traction member includes a proximal end coupled to the shaft.

29. (currently amended) A medical device, comprising:  
a catheter shaft having a guidewire lumen defined therein;  
a balloon coupled to the shaft, the balloon being substantially coaxially arranged with respect to at least a region of the guidewire lumen; and  
a traction member including an elongate member having a proximal end and a distal end extending longitudinally exterior of the balloon, the having a distal end of the traction member coupled to the balloon catheter at a position proximate a distal end of the shaft and extending in the proximal direction and along an exterior surface of the balloon; and  
wherein the proximal end of the traction member ~~includes a proximal end that~~ is not attached to the shaft and is disposed adjacent the balloon.

30. (original) The medical device of claim 29, wherein the proximal end of the traction member is disposed adjacent a proximal waist of the balloon.

Appl. No. 10/828,572

Amdt dated October 5, 2006

Reply to Final Office Action of June 8, 2006

31. (original) The medical device of claim 29, wherein the proximal end of the traction member is disposed adjacent a midpoint of the balloon.

32. (original) The medical device of claim 29, wherein the proximal end of the traction member is disposed adjacent a distal waist of the balloon.

33. (currently amended) A balloon catheter for expanding an intravascular lesion, comprising:

an elongate catheter shaft having a distal end, an inflation lumen defined therein, and a guidewire lumen defined therein;

a balloon coupled to the shaft and disposed adjacent the distal end of the shaft; and

means for increasing the traction between the balloon and the intravascular lesion, wherein the means for increasing the traction between the balloon and the intravascular lesion includes one or more non-woven wires ~~coupled~~ affixed to the distal end of the catheter shaft and extending proximally therefrom.

34. (currently amended) A balloon catheter for expanding an intravascular lesion, comprising:

an elongate catheter shaft having a distal end and a guidewire lumen defined therein;

a balloon coupled to the shaft and disposed adjacent the distal end of the shaft, the balloon being substantially coaxially arranged with at least a region of the guidewire lumen; and

means for increasing the traction between the balloon and the intravascular lesion, wherein the means for increasing the traction between the balloon and the intravascular lesion includes one or more non-woven wires ~~coupled~~ affixed to the distal end of the catheter shaft and extending proximally therefrom.

35. (currently amended) A method for treating an intravascular lesion, comprising the steps of:

providing a balloon catheter, the balloon catheter including a catheter shaft having a guidewire lumen defined therein, a balloon coupled to the shaft substantially coaxially arranged with respect to at least a region of the guidewire lumen, and a traction member including one or

Appl. No. 10/828,572  
Amdt. dated October 5, 2006  
Reply to Final Office Action of June 8, 2006

more non-woven wires having a distal end ~~coupled~~ affixed to the shaft at a position distal of the balloon and extending in the proximal direction and along the balloon;

wherein the traction member further comprises a proximal end that is free from attachment to the shaft;

advancing the balloon catheter through a blood vessel to a position adjacent a target site;  
and

inflating the balloon, whereby the traction member is disposed between the balloon and the target site and improves the traction between the balloon and the target site.

36. (new) The balloon catheter of claim 1, wherein the traction member includes one or more non-woven wires.

37. (new) The balloon catheter of claim 1, wherein the traction member extends longitudinally over at least a portion of the balloon.

38. (new) The balloon catheter of claim 13, wherein the traction member extends longitudinally over at least a portion of the balloon.